

## Official Gazette for Kokai Patent Applications, Front Page

(11) Publication no.: Unexamined Patent Application Publication No. H06-333459  
 (43) Disclosure date: December 02, 1994

(51) Int. Cl.<sup>5</sup>

H01H 13/70  
 21/00 330

(21) Application no.: Patent Application No. H05-118405  
 (22) Applic. date: May 20, 1993

(71) Applicant: Canon Inc.  
 (72) Inventor(s): Masakazu Furuyama

(54) Pushbutton Switch Device

(57) [Abstract]

[Constitution] When an operation part 21a of a dial key 3a is pushed with a finger or the like, a corresponding key is lowered by the hinge work of a supporting piece 7, and a push part 15 of a rubber sheet 14 at a position corresponding to the pushed key is pushed to bend a thin-walled part 16 for deformation, and a movable contact 17 provided on the back surface of the rubber sheet 14 contacts a fixed contact 19 on a printed-circuit board 18, thereby resulting in the ON state. Also, when the finger or the like is removed from the operation part 21a of the dial key 3a, the thin-walled part 16 of the rubber sheet 14 is returned to the original condition, and each contact is separated, thereby resulting in the OFF [state].

[Effects] According to the present invention, the number of components is reduced, enabling improved ease of assembly. Moreover, by adopting a structure in which a flexible sheet member (e.g., a rubber sheet) is held between a printed circuit board and a pushbutton, when the pushbutton is pressed and the thin-walled part of the said sheet member is bent and deformed, the depressing force is transmitted reliably, thereby yielding a stable click feel.

